

QC STL PRO-2.5X Specifications

Air Flow	Hi: 2,541 CFM / Low: 2,018 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 1,920 CFM / Low: 1,510 CFM	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 847 SQFT to 1,271 SQFT	
Energy Use	Hi: 157 Watts / Low: 82.3 Watts	
Amps	Hi: 2.12 / Low: 1.12	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	2	
dBA	Hi: 42.7 / Low: 37.2	
Minimum Attic Clearance	34"	
Duct Diameter	16"	
Duct Length	6 feet	
Motor Head Diameter	16 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Sold Separately)	Included: 8 Hr Electronic Timer & HI-LOW-OFF switch Optional: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	3.39 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 18 1/4"	
Removable Grille Outside Dimension	16" x 20"	
Shipping Weight	49 lbs.	
Box Dimensions	24" x 20" x 38"	
In The Box	-QC STL PRO-2.5X Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -6 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

QC STL PRO-2.5X
QuietCool Original Classic Line