



**QC TRI PRO-1.5X**  
**QuietCool Trident Pro Line**

**QC TRI PRO-1.5X Specifications**

|  |   |  |
|--|---|--|
| Air Flow   | 1,498 CFM   |  |
| HVI-916 Airflow (for CA Title 24 New Construction) | 1,110 CFM   |  |
| Recommended SQFT Coverage @ 2-3 CFM per SQFT       | Covers 499 SQFT to 749 SQFT   |  |
| Energy Use   | 115 Watts   |  |
| Amps   | 1.19  |  |
| Motor Voltage                                      | 120 VAC, 60 Hz  |  |
| # of Speeds  | 1   |  |
| dBA  | 37.4  |  |
| Minimum Attic Clearance                            | 32"   |  |
| Duct Diameter                                      | 14"   |  |
| Duct Length  | 6 feet  |  |
| Motor Head Diameter                                | 14 1/2"   |  |
| Motor Head Length                                  | 13 1/2"   |  |
| Dampers  | Barometric Pressurized R5 Dampers   |  |
| Controls (Sold Separately)                         | Included: 8 Hr Electronic Timer<br>Optional: IT-36002 QuietCool RF Wireless Control Kit |  |
| Warranty   | 15 Years  |  |
| Framing  | None Required   |  |
| Joist Cutting                                      | None Required; fits 16" or 24" on center  |  |
| Minimum Suggested Attic Venting                    | 2 SQ FT net free area   |  |
| Ceiling Rough Opening                              | 14 1/4" x 14 1/4"   |  |
| Removable Grille Outside Dimension                 | 16" x 16"   |  |
| Shipping Weight                                    | 43 lbs.   |  |
| Box Dimensions                                     | 20" x 20" x 38"   |  |
| In The Box   | -QC TRI PRO-1.5X Motorhead<br>-Ceiling Grille<br>-Cut-out Template<br>-Window Locks     | -Damper Box<br>-6 Foot Duct<br>-Accessory Bag<br>-Controls |



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)